

## **INDUSTRIAL TUMBLER DRYER**

TX RANGE **TX9** 

9 KG 20LB



## **FEATURES**

- Standard stainless steel drum
- Anthracite grey skin plate
- Inox top panel
- Easy-to-use microprocessor (ECT)
- DimpleDry™ with innovative bulged drum
- Axial airflow
- 210° door opening for easy loading and unloading
- Intuitive control with simple selection and 3 programs

## **OPTIONS**

- Stainless steel front
- Reverse drum
- Residual moisture control Sensodry®:
  - safe drying of delicate linen
  - humidity detection in %
- Heating power from 6 (kW) up to 12 (kW), to match various installation requirements
- Coin operated version







20% LOWER ENERGY CONSUMPTION\*



30% FASTER EVAPORATION\*





## DimpleDry™

DimpleDry is the combined effect of a deeper drum with a bulged drum shape, improving the airflow, drying efficiency and fabric care.

<sup>\*</sup>vs previous generation, Duration of total dry cycle time from (55±1)% initial humidity to (8+1-0)% with no cool down time. Test performed in our lab according to ISO9398-2:2003 standard for 100% cotton towels, with 12Kw.

ТҮРЕ		TX9 EL	TX9 HP
DRUM & CAPACITY			
Drum capacity	kg/lb	9	
Drum volume	L	195	
Drum diameter	mm	670	
Drum depth	mm	555	
Drum type		DimpleDry	
DOOR			
Door opening Ø	mm	500	
Opening direction		Right (reversible)	
Door opening angle		210°	
DRYING PERFORMANCE			
Airflow type		Axial	
Airflow	m3/h	300	
HEATING			
Heating type		Electric	Heat pump
Heating power	kW	6/9/12	1,5
Total power supply	kW	6,4 / 9,4 / 12,4	2
Electrical connection		3x 220-230V 50Hz 3x 220-230V 60 Hz 3x 240V 50Hz 3x 380-415V +N 50 Hz 3x 380-415V +N 60Hz 3x 380-415V 50 Hz 3x 380-415V 60Hz 3x 440V 60Hz	3x 220-240V 50Hz 3x 380-415V +N 50Hz
MOTOR			
Fan	kW	0,25	0,17
Drive	kW	0,25	0,25
CONNECTION			
Exhaust		150 mm	n/a
Water vavle conection		n/a	2x 1"
Condensate drain		n/a	16 mm
PROGRAMMER		Easy Control	
NOISE			
Drying sequence	dB	55	54
DIMENSIONS			
HxWxD	mm	1150 x 710 x 945	1725 x 710 x 925
Net weight	kg	125	193
TRANSPORT DATA			
Packed HxWxD	mm	1253 x 752 x 970	1815 x 752 x 970
Gross weight (foil)	kg	135	208

