

Drying cabinet

DC 4



FEATURES

- Flexible construction allows hanging bars to slide easily forward for easy access to garments or down for more space.
- Easy to install; the evacuating channel is connected to the ventilation system and the humid air is transported out of the room.
- All electrical components are placed on the top which makes it easy to maintain.
- Pull-out hanging system
- 3 temperatures; high, normal, low
- Energy efficient
- Timer adjustable up to 4 hours
- Overheat protection
- IP 24 classification. CE-approved
- The door can be ordered right- or left-hanged

OPTIONS

- Baskets to drip dry on a flat surface
- Hangers for small items (door frame)

MARKETS

Day care center, Schools, Road workers dressing room, Ships, Airports, Ski resorts, Campings, Security

Main specifications		DC4
Loading capacity	kg/lbs	4 kg/8,8 lbs
Drying capacity	g/min*	17
Hanging length	m/feet	16/52,5
Drying time, economy 30° C	min*	180
Drying time, express 45° C	min*	120
Heating effect	kW	1,5
Total effect	kW	1,535
Energy consumption economy /kg	kWh	0,5
Energy consumption express /kg	kWh	0,6
*Valid for high-spinned textiles.		

Technical specification		DC4
ELECTRICAL CONNECTIONS		
Electrical connection		1N, 230 V, 50 Hz
Fuse	A	10
Total effect	kW	1,535
Heating elements	kW	1,5
AIR CONNECTIONS		
Outlet exhaust	ø mm/inch	100/3,94
Outlet air flow	m³/h	50
Pressure drop	max Pa	60
Dewatering capacity	g/min	17
SOUND LEVEL		
Airborne sound level	dB(A)	60
SHIPPING DATA		
Net	kg/lbs	61/134,5
Crated	kg/lbs	4/8,8
Shipping data net	kg/lbs	65/143
Shipping volume	m³	0,2
OPTIONAL EXTRAS		
Air exchanger 1 vent., 125 mm/4,9 inch	part number	141009
Air exchanger 2 vent., 160 mm/6,3 inch	part number	141018
DIMENSIONS		
Width	mm/inch	595/23,4
Depth	mm/inch	615/24,2
Height	mm/inch	1915/75,4

06-2010 / 538253

The company Primus preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.

www.primuslaundry.com

